

# Bollard 3



## Application:

7" Diameter round bollard. These fixtures provide uniform illumination, superior spacing and remarkable brightness control. Each bollard features rugged construction, and comes supplied with silicone gasketing to assure years of trouble free service.

### Features:


- Provides 360 deg. Of low level lighting
- Extruded aluminum housing with flush mounting base
- Vandal resistant screws
- Powder coat finish
- Clear polycarbonate lens
- Ballast tray for ease of maintenance
- Standard color is bronze also available in black and white.

Job Information	
Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	



Height	Width	CFL	MH	HPS	EPA	Weight
43"	7"	42	70	70		22 lbs.

### Isolux Curves



70 watt metal halide internal louvers

### ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
<ul style="list-style-type: none"> <li>• <b>BOL3</b></li> </ul>	360 deg. Low Level lighting <ul style="list-style-type: none"> <li>• <b>(360)</b></li> </ul>	35w <ul style="list-style-type: none"> <li>• <b>(35)</b></li> </ul> 50w <ul style="list-style-type: none"> <li>• <b>(50)</b></li> </ul> 70w <ul style="list-style-type: none"> <li>• <b>(70)</b></li> </ul> 1x26w <ul style="list-style-type: none"> <li>• <b>(26)</b></li> </ul> 1x32w <ul style="list-style-type: none"> <li>• <b>(32)</b></li> </ul> 1x42w <ul style="list-style-type: none"> <li>• <b>(42)</b></li> </ul>	HPS <ul style="list-style-type: none"> <li>• <b>(HPS)</b></li> </ul> Pulse Start Metal Halide <ul style="list-style-type: none"> <li>• <b>(PS)</b></li> </ul> Compact Fluorescent <ul style="list-style-type: none"> <li>• <b>(CFL)</b></li> </ul>	120 Volts <ul style="list-style-type: none"> <li>• <b>(120)</b></li> </ul> 208 Volts <ul style="list-style-type: none"> <li>• <b>(208)</b></li> </ul> 240 Volts <ul style="list-style-type: none"> <li>• <b>(240)</b></li> </ul> 277 Volts <ul style="list-style-type: none"> <li>• <b>(277)</b></li> </ul> 480 Volts <ul style="list-style-type: none"> <li>• <b>(480)</b></li> </ul> Multi-Tap Ballast Factory wired at 277v unless otherwise specified.	43" <ul style="list-style-type: none"> <li>• <b>(43)</b></li> </ul>	Bronze <ul style="list-style-type: none"> <li>• <b>(BZ)</b></li> </ul> White <ul style="list-style-type: none"> <li>• <b>(WT)</b></li> </ul> Black <ul style="list-style-type: none"> <li>• <b>(BK)</b></li> </ul> Custom Color <ul style="list-style-type: none"> <li>• <b>(CC)</b></li> </ul> Consult Factory	Internal 180 Deg. Shield <ul style="list-style-type: none"> <li>• <b>(180)</b></li> </ul>

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions