

Econo Star

Benefits:

- Local utility rebates
- 50% - 75% energy savings
- Improved light uniformity
- High efficiency luminaire with 2 thru 6 lamp in 14-49watts
- Cold weather electronic ballast
- Superior visual acuity
- Improved lumen maintenance
- Longer service life
- No out of pocket expense
Pay with your monthly energy savings

Features:

- Uses T5HO technology to get comparable light levels
- Precision fabricated and formed aluminum housing
- Powder coat finish provides excellent corrosion resistance and durability
- Heavy duty aluminum body provides excellent heat dissipation, maximizing ballast & lamp life
- Forward throw optics



Heavy Cast Fitter



Fully Adjustable

FLUORESCENT ADVANTAGES

The Econo Star fluorescent family of luminaires have several advantages over traditional HID; energy savings, instant on and re-strike, improve visual acuity, better lumen maintenance, longer lamp life, and more economical controls and compatibility. Fluorescent also has a proven track record and a cost advantage over some emerging light source technologies.

- Provides auto dealers and other retailers a viable option to replace short life 1000 watt metal halide lamps that operate at 1080 watts.
- Offered with a full range of custom color to integrate into your project color palette.
- Sculpted sleek look for architectural appeal and minimize wind loading.
- Heavy duty aluminum body and mounting arm provides excellent heat dissipation and maximum ballast life.
- Post production powder coat finish provides excellent corrosion resistance and durability.
- Easy access to the lamps and electrical cavity. The heavy duty door frame provides access from below, opens easily, and secures tightly when closed.
- T5 application = 36,000 hours (based on 12 hour starts), lower energy consumption, no color shift, 85+ CRI full spectrum color.
- -20 deg. starting: Enhanced cold weather performance using the amalgam technology T5HO lamps (optional)

Existing Area Light System	Lamp Qty & Type	Initial Lamp Lumens	Lumen Maintenance	EOL(1) Lumens All Lamps	Total Fixture Lumens	Ballast Factor	Fixture Efficiency	EOL (1) Lumens Per Fix.	S/P (2) Ratio	Net (3) EOL Lumens	Fix. Input Watts
MH400	1/Std. MH400	38,000	58%	22,040	22,040	1.00	0.75	16,530	1.49	22,561	458
HPS 400	1/Std. HPS400	50,000	70%	35,000	35,000	1.00	0.75	26,250	0.62	18,080	464
MH1000(16k hrs)	1/Std. MH1000	110,000	26%	28,600	28,600	1.00	0.75	21,450	1.49	29,276	1080
MH1000(12k hrs)	1/Std. MH1000	110,000	37%	40,700	40,700	1.00	0.75	30,525	1.49	41,662	1080
MH1000(8k hrs)	1/Std. MH1000	110,000	50%	55,000	55,000	1.00	0.75	41,250	1.49	56,300	1080
MH1000(4k hrs)	1/Std. MH1000	110,000	72%	79,200	79,200	1.00	0.75	59,400	1.49	81,072	1080

Proposed Area Light System	Lamp Qty & Type	Initial Lamp Lumens	Lumen Maintenance	EOL(1) Lumens All Lamps	Total Fixture Lumens	Ballast Factor	Fixture Efficiency	EOL(1) Lumens Per Fix.	S/P(2) Ratio	Net(3) EOL Lumens	Fix. Input Watts
5L-T5HO	5/F54T5HO	5,000	95%	4,750	23,750	1.00	0.82	19,475	1.62	28,331	293
6L-T5HO	6/F54T5HO	5,000	95%	4,750	28,500	1.00	0.82	23,370	1.62	33,997	351

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions