



La Jolla

SPECIFICATIONS:

Housing:

A weather tight unit fabricated from .080" thick aluminum continuous heliarc welded at all seams. Features a .125" ballast plate and a .250" Reinforcing plate for arm attachment, tapped to accept the mounting arm's thru-bolts, so there is no need to open the fixture during mounting.

Lens & Removable Door Assembly:

Hinged door assembly formed from one piece .080" corrosion resistant aluminum with stainless steel fasteners. The lens is a clear tempered flat Glass, secured by galvanized lens clips and sealed with silicone gasket to ensure protection from the harshest environment.

Optics:

A Horizontal segmented reflector with specular aluminum finish available in (3) distribution patterns

Electrical Assembly:

HID ballast constant wattage auto-transformer high power factor core and coil type, rated -20 degrees Fahrenheit starting temperature. Integrally Mounted in the luminaire and completely prewired. Each ballast assembly is thoroughly tested prior to shipment. Ballast And Electrical Components are "UL" Listed.

Lamp Socket:


Standard LPS socket

Finish:

Chemically pretreated through a multiple stage washer, thermoset polyester textured Powder Coat min. 3-5 mil. Thickness. Oven baked at 400 degrees Fahrenheit to insure maximum adherence.

Job Information	
Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	

DIMENSIONAL DRAWINGS



Fixture	A	B	C	Maximum Watts	Lbs.	EPA
LJA-1	24"	15"	9"	55w	45	2.0
LJA-2	29"	15"	9"	90w	50	2.3
LJA-3	29"	20"	9"	2 x 90w	60	3.5
LJA-4	52"	15"	9"	180w	70	3.7

ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
<ul style="list-style-type: none"> LJA-1 LJA-2 LJA-3 LJA-4 	<ul style="list-style-type: none"> TYPE II (T2) TYPE III (T3) TYPE V (T5) 	<ul style="list-style-type: none"> 35w (35) 55w (55) 90w (90) 2-90w (290) 135w (135) 180w (180) 	<ul style="list-style-type: none"> Low Pressure Sodium (LPS) T5 Linear Fluorescent (LF) Consult Factory 	<ul style="list-style-type: none"> 120 Volts (120) 208 Volts (208) 240 Volts (240) 277 Volts (277) 480 Volts (480) Multi-Tap Ballast Factory wired at 277v unless otherwise specified. 	<ul style="list-style-type: none"> Bolt on Arm 6" (BOA6) Bolt on Arm 10" (BOA10) Parallel Pole Mount (PM) Parallel Wall Mount (PW) Perpendicular Wall Mount (PWM) Slip Fitter (SF) 	<ul style="list-style-type: none"> Bronze (BZ) White (WT) Black (BK) Green (GN) Grey (GY) Custom Color (CC) Consult Factory 	<ul style="list-style-type: none"> Photocell 120 - 480v (PC) Photocell & Shorting cap (PCSC) House Side Light Shield (LS) Round Pole adaptor (RPA) Wall Plate (WP)

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions