


Lyon

SPECIFICATIONS:

Job Information

Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	

DIMENSIONAL DRAWINGS



Height	Diam.	Depth	MH	HPS	EPA	Weight
15.5"	27.5"		175	150	1.68	25 lbs.

Housing:

Housing and Hood Made of Durable Spun corrosion Resistant Aluminum Construction, Fully Gasketed to Maintain Weather Tight Seal.

Lens:

Clear Acrylic Diffuser, Louvered Optical Stack, Bright Dipped Anodized Louver Assembly, Provides Wide Light Distribution and Precise Cutoff.

Reflector:

Underside of Hood is Powder Coated Specular White for maximum light Distribution

Electrical Assembly:

HID ballast constant wattage auto-transformer high power factor core and coil type, rated -20 degrees Fahrenheit starting temperature. Integrally Mounted in the luminaire and completely prewired. Each ballast assembly is thoroughly tested prior to shipment. Ballast And Electrical Components are "UL" Listed.

Lamp Socket:

Porcelain socket pulse rated for HPS & MH lamps. lamp included.

Finish:

Attractive dark bronze, white, black polyester powder coated finish for excellent impact, corrosion and UV resistance

ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
<ul style="list-style-type: none"> Lyon 	Internal Louver <ul style="list-style-type: none"> (IL) 	70w <ul style="list-style-type: none"> (70) 100w <ul style="list-style-type: none"> (100) 150w <ul style="list-style-type: none"> (150) 175w <ul style="list-style-type: none"> (175) Compact Fluorescent 2x42w <ul style="list-style-type: none"> (242) 	High Pressure Sodium <ul style="list-style-type: none"> (HPS) Metal Halide <ul style="list-style-type: none"> (MH) Compact Fluorescent <ul style="list-style-type: none"> (CFL) 	120 Volts <ul style="list-style-type: none"> (120) 208 Volts <ul style="list-style-type: none"> (208) 240 Volts <ul style="list-style-type: none"> (240) 277 Volts <ul style="list-style-type: none"> (277) 480 Volts <ul style="list-style-type: none"> (480) Multi-Tap Ballast Factory wired at 277v unless otherwise specified.	Tenon Adaptor 2 3/8" <ul style="list-style-type: none"> (TA238) Tenon Adaptor 3" <ul style="list-style-type: none"> (TA3) Wall mount <ul style="list-style-type: none"> (WM) 	Bronze <ul style="list-style-type: none"> (BZ) White <ul style="list-style-type: none"> (WT) Black <ul style="list-style-type: none"> (BK) 	Photo Cell 120 - 480v <ul style="list-style-type: none"> (PC__) Pier Mount <ul style="list-style-type: none"> (PM) House side Shield <ul style="list-style-type: none"> (HSS)

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions