



Parking Bright

SPECIFICATIONS:

Job Information	
Project:	Date:
Location:	
Fixture Type:	Cat. #
Lamp:	Volts:
Options & Accessories:	
DIMENSIONAL DRAWINGS	

Housing:

A weather tight unit fabricated from .080" thick aluminum continuous heliarc welded at all seams. Features a .125" ballast plate and a .250" Reinforcing plate for arm attachment, tapped to accept the mounting arm's thru-bolts, so there is no need to open the fixture during mounting.

Lens & Removable Door Assembly:

Hinged door assembly formed from one piece .080" corrosion resistant aluminum with stainless steel fasteners. The lens is a clear tempered flat Glass, secured by galvanized lens clips and sealed with silicone gasket to ensure protection from the harshest environment.

Optics:

A Vertical segmented reflector with specular aluminum finish available In (4) distribution patterns

Electrical Assembly:


HID ballast constant wattage auto-transformer high power factor core and coil type, rated -20 degrees Fahrenheit starting temperature. Integrally Mounted in the luminaire and completely prewired. Each ballast assembly is thoroughly tested prior to shipment. Ballast And Electrical Components are "UL" Listed.

Lamp Socket:

Porcelain Socket pulse rated at 5K & 600V for HPS, MH & PS lamps.

Finish:

Chemically pretreated through a multiple stage washer, thermoset polyester textured Powder Coat min. 3-5 mil. Thickness. Oven baked at 400 degrees Fahrenheit to insure maximum adherence.



Fixture	A	B	C	Maximum Watts	LBS
PBT-1	24"	16"	8"	400w	40
PBT-2	27"	21"	9"	1000w	70

ORDERING INFORMATION:

Model	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
<ul style="list-style-type: none"> PBT-1 PBT-2 	TYPE II • (T2)	70w • (70)	High Pressure Sodium • (HPS)	120 Volts • (120)	Bolt on Arm 6" • (BOA6)	Bronze (BZ)	Photo Cell 120 - 277v • (PC__)
	TYPE III • (T3)	100w • (100)	Metal Halide • (MH)	208 Volts • (208)	Bolt on Arm 10" • (BOA10)	White (WT)	House Side Light Shield • (HSS)
	TYPE IV • (T4)	150w • (150)	Pulse Start • (PS)	240 Volts • (240)	Wall Mount • (WM)	Black • (BK)	Round Pole adaptor • (RPA)
	TYPE V • (T5)	175w • (175)		277 Volts • (277)		Green • (GN)	Wall Plate • (WP)
		250w • (250)		Multi-Tap • (MT)		Grey • (GY)	
		320w • (320)		480 Volts • (480)		Custom Color • (CC)	
		400w • (400)		Multi-Tap Ballast Factory wired at 277 v unless otherwise specified.		Consult Factory	
		1000w • (1000)					

Direct Lighting Sales reserves the right to make modifications or changes to any of its products without prior written notification and without incurring obligation. Actual performance can vary depending on surrounding conditions